exciters/all-in-one transmitters

> Easy maintenance exciter series
> All-in-One transmitter series
> All-in-One high fidelity series

TEX3500LCD

TEX3500LCD front view

Features

- **PRIMARY APPLICATION:** high quality at a very attractive price. Ideal for use as transmitters in stand-alone applications. Adjustable power output from 20 to 100%.
- **AUDIO PERFORMANCE:** low distortion and intermodulation values and a high noise/signal ratio.
- **HARDWARE FEATURES:** compact and indeformable thanks to the stainless steel chassis, in 3 rack units only.
- **USER-FRIENDLY FEATURES:** four pushbuttons for user/device interaction and software that offers a simple, intuitive interface.
- **EASE OF MAINTENANCE:** advanced module engineering ensures extreme of access and simple maintenance.
- **OPERATING EFFICIENCY:** incorporate 3 PFC (Power Factor Corrector) power supplies in a redundant configuration, that provides the utmost efficiency for enhanced energy saving and environmental protection, which added to LD-MOSFET technology ensure high efficiency, better than 70% across the bandwidth.
- **RELIABILITY/CONTINUITY:** APC (Automatic Power Control) and Foldback protection ensure reliable operation under any operating conditions.
- **INTERFACE CONTROL:** total control thanks to microprocessor easily programmed from menu with all key parameters displayed on LCD.
- **INPUT/OUTPUT INTERFACE:** built-in high-performance stereo coder, L&R analogue audio inputs, Mono inputs, MPX composite signal and auxiliary inputs for SCA / RDS signals.
- **RDS APPLICATION:** built-in RDS encoder with UECP standard functions (option).
- **REMOTE CONTROL:** built-in telemetry system via GSM modem, battery and battery charger or via WEB or via SNMP (option).
- **REGULATORY COMPLIANCE:** state-of-the-art technology in full compliance with EC, FCC and CCIR standards.

Caratteristiche

- ***PRIMARY APPLICATION:*** *alta qualità ad un prezzo estremamente contenuto, ideali come trasmettitori in applicazioni stand-alone con potenza di uscita regolabile dal 20 al 100%.*
- ***AUDIO PERFORMANCE:*** *bassi valori di distorsione, di intermodulazione e alto rapporto segnale rumore.*
- ***HARDWARE FEATURES:*** *compatto, indeformabile e leggero perché realizzati in chassis di acciaio inox, in sole 3 unità rack.*
- ***USER-FRIENDLY FEATURES:*** *quattro tasti a pressione per l'interazione fra l'utente e l'apparato unita ad un software intuitivo e semplificato.*
- ***EASE OF MAINTENANCE:*** *estrema accessibilità e semplicità di manutenzione grazie ad una avanzata ingegnerizzazione modulare dell'apparato.*
- ***OPERATING EFFICIENCY:*** *per un risparmio di risorse energetiche e ambientali, utilizzano 3 alimentatori PFC (Power Factor Corrector) in configurazione ridondante che sommato alla tecnologia LD-MOSFET garantisce rendimenti elevati, superiori al 70% su tutta la banda.*
- ***RELIABILITY/CONTINUITY:*** *elevata continuità di esercizio garantita in qualsiasi condizione di lavoro attraverso un controllo automatico APC ed una protezione di Foldback.*
- ***INTERFACE CONTROL:*** *controllo completo basato su microprocessore e da menu con lettura su display LCD di tutti i parametri principali.*
- ***INPUT/OUTPUT INTERFACE:*** *stereo coder integrato ad elevate prestazioni, ingressi audio analogici L&R, Mono e segnale composito MPX ed ausiliari per segnali SCA / RDS.*
- ***RDS APPLICATION:*** *encoder RDS integrato UECP standard (versione vendibile opzionalmente).*
- ***REMOTE CONTROL:*** *sistema di telemetria integrato via modem GSM, batteria e caricabatteria o via WEB o via SNMP (versione vendibile opzionalmente).*
- ***REGULATORY COMPLIANCE:*** *tecnologia moderna e pienamente rispondente alle normative EC, FCC ed CCIR.*

R.V.R. ELETTRONICA
Via del Fonditore, 2/2c • Zona Industriale Roveri • 40138 Bologna • Italy
Phone: +39 051 6010506 • Fax: +39 051 6011104 • info@RVR.it • www.RVR.it

ISO 9001:2000 certified since 2000
Member of CIQ Federation
RINA ISO 9001:2000 Certified Quality System

BROADCAST EQUIPMENT

Oirt, JPN & China Band others on request

Technical specifications

		/ 95% relative Humidity non condensing
		From software, with 10 kHz steps
		150 kHz Stereo, 180 kHz Mono/MPX
		0 µS, 50 µS (CCIR), 75 µS (FCC)

All pictures are RVR's property and they are only indicative and not binding. The pictures can be modified without notice.
These are general specifications. They show typical values and are subject to change without notice.

CE 99/5/CE **Revision: 02/16**

Ordering Information

	AES/EBU audio input option for TEX LCD Series. *Opzione ingresso audio AES/EBU per famiglia T*
	coded station ID code generated through FSK (Frequency Shift Keying) function. *Codice identificativo della radio via codice Morse attraverso la funzione FSK(Frequency Shift Keying).* *
	in RDS system with standard basic functions. *Sistema RDS integrato con funzioni base stan*
	Internal telemetry system without modem. *Sistema di telemetria interna senza modem.*
	Telemetry system via internal GSM modem. Battery and battery charger included. *Sistema di telemetria attraverso modem GSM interno. Batteria*
	Basic telemetry system via the Internet.
	Telemetry system via the Internet. Battery and battery charger included. *Sistema di telemetria attraverso internet. Batteria e caricabatterie incluse.*

Si prega di specificare il nome della stazione in fase di ordine d'acquisto